

IF4 SET-UP SHEET

NAME

DATE

TRACK

EVENT

QUAL. POSITION FINAL POSITION BEST LAP sec RACE LENGTH min

TEMPERATURE AIR TEMPERATURE TRACK

TRACK

TRACK SURFACE ☐ ASPHALT ☐ CARPET

TRACK LAYOUT ☐ TECHNICAL ☐ MIXED ☐ FAST

TRACTION ☐ LOW ☐ MEDIUM ☐ HIGH

TRANSMISSION

FRONT ☐ SOLID AXLE ☐ STEEL ☐ ALUMINUM

REAR ☐ GEAR DIFFERENTIAL ☐ GEAR DIFFERENTIAL

OIL OIL

PINION GEAR SPUR GEAR FINAL DRIVE RATIO

FRONT	SHOCKS	REAR
	SHOCK TYPE	
	SPRINGS	
	OIL	
	REBOUND (%)	
☐ 3 HOLES ☐ 1.1mm ☐ 4 HOLES ☐ 1.2mm ☐ mm	PISTONS	☐ 3 HOLES ☐ 1.1mm ☐ 4 HOLES ☐ 1.2mm ☐ mm
	LENGTH	
	OTHER	
	ANTI-ROLL BAR	

FRONT	TIRES	REAR
	TIRES	
	INSERTS	
	WHEELS	
	ADDITIVE	
	ADDITIVE TIMING	

SUSPENSION HOLDER

FF HOLDER ☐ 0.0 ☐ 4.5 ☐ 6.0 ☐ LOW

ECENTRIC BUSHINGS ☐ 0.5 ☐ 0.5 ☐ 1 ☐ 1

RF HOLDER ☐ 0.0 ☐ 4.5 ☐ 6.0 ☐ LOW

FR HOLDER ☐ 0.0 ☐ 4.5 ☐ 6.0 ☐ LOW

ECENTRIC BUSHINGS ☐ 0.5 ☐ 0.5 ☐ 1 ☐ 1

RR HOLDER ☐ 0.0 ☐ 4.5 ☐ 6.0 ☐ LOW

OTHER

MOTOR	TIMING
ESC	BATTERIES
BODY	WING

COMMENTS

C-HUB ☐ STANDARD(N)

SHIM mm

FRONT mm

REAR mm

SHIM mm

REAR HUB ☐ T012 (H) ☐ VZ (G) ☐ VZ (H)

STEERING BLOCK ☐ T012 (H) ☐ VZ (G) ☐ VZ (H)

FRONT ARM ☐ STANDARD(H)

REAR ARM ☐ STANDARD(H)

OFFSET ☐ STANDARD (5.0) ☐ 4.5 ☐ 4.25

FRONT mm **DOWNSTOP** mm **REAR** mm

CAMBER deg

FRONT deg **REAR** deg

UPPER SHOCK POSITION

FRONT SHOCK TOWER ☐ STANDARD ☐ Ver. B

REAR SHOCK TOWER ☐ STANDARD ☐ Ver. B

LOWER SHOCK POSITION 33.0 28.6 32.0 27.6

FRONT mm **RISE HEIGHT** mm **REAR** mm

LOWER SHOCK POSITION 31.7 36.1 40.5 30.7 35.1 39.5

PRS SYSTEM Passive Rear Steering

REAR **SHIM** mm

C-HUB ☐ ALUMINUM

REAR ARM ☐ STANDARD(H)

STEERING BLOCK ☐ T102 (H) ☐ VG (G) ☐ VG (H)

STEERING BLOCK POSITION ☐ UP ☐ DOWN

OFFSET ☐ STANDARD ☐ 4.5 ☐ 4.25

TOE OUT deg

TOE IN deg

BUMP STEER SHIM mm

STEERING SYSTEM ☐ FLOATING ☐ CHASSIS MOUNTED

BELL CRANK ☐ STANDARD ☐ ALUMINUM

SERVO HONE ☐ STANDARD ☐ ALUMINUM ☐ 17mm ☐ 19mm ☐ 18mm ☐ 20mm

CHASSIS FLEX ☐ SCREW USED ☐ SCREW NOT USED

CHASSIS FLEX ☐ SCREW USED ☐ SCREW NOT USED

CHASSIS FLEX ☐ SCREW USED ☐ SCREW NOT USED

CHASSIS FLEX ☐ SCREW USED ☐ SCREW NOT USED

TOP DECK ☐ STANDARD(2mm) ☐ 1.6mm

MAIN CHASSIS ☐ STANDARD(2.25mm) ☐ ALUMINUM

BATTERY STRAP ☐ USE HOLDER ☐ VERTICAL ☐ HORIZONTAL

WHEELBASE SHIM mm

DIFF. POSITION ☐ UP ☐ DOWN

TOP DECK FLEX ☐ SCREW USED ☐ SCREW NOT USED

SHIMS UNDER TOP DECK ☐ YES ☐ NO mm

BALANCE g

BALANCE g

BALANCE g

BALANCE g