

# IF14 SET-UP SHEET

NAME

DATE

TRACK

EVENT

QUAL. POSITION  FINAL POSITION  BEST LAP  sec RACE LENGTH  min

TEMPERATURE AIR  TEMPERATURE TRACK

**TRACK**

TRACK SURFACE ☐ ASPHALT ☐ CARPET

TRACK LAYOUT ☐ TECHNICAL ☐ MIXED ☐ FAST

TRACTION ☐ LOW ☐ MEDIUM ☐ HIGH

**FRONT TRANSMISSION REAR**

☐ SOLID AXLE ☐ ONE WAY ☐ GEAR DIFFERENTIAL

OIL  OIL

PINION GEAR  SPUR GEAR  FINAL DRIVE RATIO

FRONT	SHOCKS	REAR
	SHOCK TYPE	
	SPRINGS	
	OIL	
	REBOUND (%)	
<input type="checkbox"/> 3 HOLES <input type="checkbox"/> 1.1mm <input type="checkbox"/> 4 HOLES <input type="checkbox"/> 1.2mm <input type="checkbox"/> mm	PISTONS	<input type="checkbox"/> 3 HOLES <input type="checkbox"/> 1.1mm <input type="checkbox"/> 4 HOLES <input type="checkbox"/> 1.2mm <input type="checkbox"/> mm
	LENGTH	
	OTHER	
	ANTI-ROLL BAR	

FRONT	TIRES	REAR
	TIRES	
	INSERTS	
	WHEELS	
	ADDITIVE	
	ADDITIVE TIMING	

**SUSPENSION HOLDER**

**FF** HOLDER ☐ 0.0 ☐ 4.5 ☐ 6.0 ☐ LOW

**RF** HOLDER ☐ 0.0 ☐ 4.5 ☐ 6.0 ☐ LOW

**FR** HOLDER ☐ 0.0 ☐ 4.5 ☐ 6.0 ☐ LOW

**RR** HOLDER ☐ 0.0 ☐ 4.5 ☐ 6.0 ☐ LOW

**OTHER**

MOTOR  TIMING

ESC  BATTERIES

BODY  WING

COMMENTS

**C-HUB** ☐ STANDARD(N)

**STEERING BLOCK** ☐ T012 (H) ☐ VZ (G) ☐ VZ (H)

**OFFSET** ☐ STANDARD (5.0) ☐ 4.5 ☐ 4.25

**FRONT** SHIM mm

**REAR** SHIM mm

**REAR HUB** ☐ T012 (H) ☐ VZ (G) ☐ VZ (H)

**OFFSET** ☐ STANDARD (5.0) ☐ 4.5 ☐ 4.25

**FRONT ARM** ☐ STANDARD(H)

**REAR ARM** ☐ STANDARD(H)

**DOWNSTOP** mm

**CAMBER** FRONT deg. REAR deg.

**UPPER SHOCK POSITION**

**FRONT SHOCK TOWER** ☐ STANDARD ☐ Ver. B

**REAR SHOCK TOWER** ☐ STANDARD ☐ Ver. B

**LOWER SHOCK POSITION**

FRONT 33.0 28.6 32.0 27.6

REAR 31.7 36.1 40.5 30.7 35.1 39.5

**RISE HEIGHT** mm

**PRS SYSTEM** Passive Rear Steering

**REAR** SHIM mm

**C-HUB** ☐ ALUMINUM

**REAR ARM** ☐ STANDARD(H)

**STEERING BLOCK** ☐ T102 (H) ☐ VG (G) ☐ VG (H)

**STEERING BLOCK POSITION** ☐ UP ☐ DOWN

**OFFSET** ☐ STANDARD ☐ 4.5 ☐ 4.25

**TOE OUT** deg.

**TOE IN** deg.

**BUMP STEER SHIM** mm

**STEERING SYSTEM** ☐ FLOATING ☐ CHASSIS MOUNTED

**BELL CRANK** ☐ STANDARD ☐ ALUMINUM

**SERVO HONE** ☐ STANDARD ☐ ALUMINUM ☐ 17mm ☐ 19mm ☐ 18mm ☐ 20mm

**CHASSIS FLEX** ☐ SCREW USED ☐ SCREW NOT USED

**CHASSIS FLEX** ☐ SCREW USED ☐ SCREW NOT USED

**ACKERMANN SHIM** mm

**UPPER BULKHEAD** mm

**LOWER BULKHEAD** mm

**ANTI-ROLL BAR** mm

**UNDER SHOCK SHIMS** mm

**MOTOR MOUNT** ☐ STANDARD ☐ OPTION

**MOTOR MOUNT FLEX** ☐ SCREW USED ☐ SCREW NOT USED

**TOP DECK** ☐ STANDARD(2mm) ☐ 1.6mm

**MAIN CHASSIS** ☐ STANDARD(2.25mm) ☐ ALUMINUM

**BATTERY STRAP** ☐ USE HOLDER ☐ VERTICAL ☐ HORIZONTAL

**WHEELBASE SHIM** mm

**DIFF. POSITION** ☐ UP ☐ DOWN

**TOP DECK FLEX** ☐ SCREW USED ☐ SCREW NOT USED

**SHIMS UNDER TOP DECK** ☐ YES ☐ NO mm

**BALANCE** g

**BALANCE** g

**BALANCE** g

**BALANCE** g