

IF18-II SET-UP SHEET ver.1.0

NAME	
DATE	
TRACK	
EVENT	

PINION	TRANSMISSION	SPUR
☐ 18T ☐ 19T ☐ 20T	☐ 1ST	☐ 60T ☐ 61T ☐ 62T
☐ 23T ☐ 24T ☐ 25T	☐ 2ND	☐ 56T ☐ 57T ☐ 58T

FRONT	SHOCKS	REAR
	SPRINGS	
	OIL	
☐ STD ☐ OPTION	☐ STD ☐ OPTION	
☐ STD ☐ HOLES	☐ STD ☐ HOLES	
	PISTONS	
	☐ STD ☐ HOLES	
	mm	mm

FRONT	ANTI-ROLL BAR	REAR
	mm	mm

FRONT	RIDE HEIGHT	REAR
	mm	mm

FRONT	WIDTH	REAR
	mm	mm

CONTROLLED	TIRES	BRAND
☐ YES ☐ NO		
FRONT	REAR	
☐ LEFT ☐ RIGHT	☐ LEFT ☐ RIGHT	
mm	mm	mm
	DIAMETER	
	mm	mm

FRONT	WHEEL PLATE	REAR
☐ YES ☐ NO		☐ YES ☐ NO

BODY

BODY SETTING
BODY POSITION mm
FRONT CARBON PLATE
CARBON PLATE ☐ YES ☐ NO (R0274)
REAR BODY MOUNT PLATE
☐ NO ☐ 0.5mm ☐ 1mm
BODY MOUNT SCREW
mm
BODY MOUNT CENTER FOAM
mm

SERVO SAVER
STEERING PLATE
☐ 9mm ☐ 10mm ☐ 11mm (STD)
POSITION
FORWARD ☐ MIDDLE ☐ BACKWARD ☐
SERVO SAVER TYPE
☐ PLASTIC (R0006) ☐ OPT (R0217) ☐ OPT (R0259)
SPACER
mm
TIGHTENING
mm

SHOCK TOWER	UPPER SUS HOLDER SIDE SCREW	UPPER SUS HOLDER & POSITION	FRONT
☐ STANDARD (R0081) ☐ OPTION (R0081W)	☐ YES ☐ NO	☐ PLASTIC ☐ PLASTIC (HARD) ☐ ALUMINIUM	CAMBER deg.
UPPER PIVOT OFFSET	TOE OUT deg.	MATERIAL ☐ NORMAL ☐ HARD	
☐ -1.0 ☐ 0 ☐ +1.0			
UPRIGHT ARM SPACER mm			
CASTER ANGLE SPACER mm			
LOWER PIVOT TYPE & SPACER HEIGHT			
☐ REVERSE 0mm=13.5 ☐ NORMAL 0mm=15.5			
SWING SHAFT			
☐ 60mm ☐ 64mm ☐ 60mm ☐ 62mm (90°)			
LOWER ARM HOLDER			
☐ PLASTIC ☐ PLASTIC (HARD) ☐ ALUMINIUM			
DOWN STOP mm			
LOWER ARM PLATE			
☐ STANDARD (OUT SIDE) ☐ OPTION (IN SIDE)			

SHOCK TOWER	BODY MOUNT POSITION	REAR
☐ STANDARD ☐ OPTION (REV)	☐ 1 ☐ 2 ☐ 3	CAMBER deg.
CENTERING POSITION mm		
UPPER SUS POSITION		
☐ WIDE ☐ NARROW		
LOWER ARM HOLDER		
☐ STANDARD ☐ OPTION		
SWING SHAFT		
☐ 54mm ☐ 54mm(90°)		
LOWER ARM PLATE		
☐ IN SIDE ☐ MIDDLE ☐ OUT SIDE (STD)		
DOWN STOP mm		
REAR HUB SPACER mm		
TOE IN deg.		
COMMENTS		

WEIGHT	CARBON STIFFENER	MAIN CHASSIS TYPE	CHASSIS
☐ MIDDLE ☐ RIGHT ☐ LEFT	☐ FRONT CARBON ☐ MIDDLE CARBON (R0282)	☐ NORMAL (R0227) ☐ SPECIAL (R0227M)	UPPER PLATE TYPE & CUT
ADDITIONAL WEIGHT g			
TOTAL CAR WEIGHT g			
BATTERY PLATE TYPE & HOLD POSITION			