

IF18 SET-UP SHEET

NAME	
DATE	
TRACK	
EVENT	

PINION	TRANSMISSION	SPUR
☐ 18T ☐ 19T ☐ 20T	☐ 1ST	☐ 60T ☐ 61T ☐ 62T
☐ 23T ☐ 24T ☐ 25T	☐ 2ND	☐ 56T ☐ 57T ☐ 58T

FRONT	SHOCKS	REAR
	SPRINGS	
	OIL	
☐ STD ☐ OPTION	O RING	☐ STD ☐ OPTION
☐ STD HOLES	PISTONS	☐ STD HOLES
mm		mm

FRONT	ANTI-ROLL BAR	REAR
mm		mm

FRONT	RIDE HEIGHT	REAR
mm		mm

FRONT	WIDTH	REAR
mm		mm

CONTROLLED	TIRES	BRAND
☐ YES ☐ NO		
FRONT		REAR
☐ LEFT ☐ RIGHT		☐ LEFT ☐ RIGHT
mm	mm	mm
	DIAMETER	

FRONT	WHEEL PLATE	REAR
☐ YES ☐ NO		☐ YES ☐ NO

BODY

BODY SETTING
BODY POSITION mm
FRONT BODY MOUNT & PLATE
☐ SHORT POST ☐ PLASTIC PLATE
☐ LONG POST ☐ CARBON PLATE
☐ NO USE PLATE
REAR BODY MOUNT PLATE
☐ NO ☐ 0.5mm ☐ 1mm
BODY MOUNT SCREW mm
BODY MOUNT CENTER FOAM mm

SERVO SAVER
STEERING PLATE
☐ 9mm ☐ 10mm ☐ 11mm (STD)
POSITION
FORWARD ☐ MIDDLE ☐ BACKWARD ☐
SERVO SAVER TYPE
☐ PLASTIC (STD) ☐ AL (R0217) ☐ AL (UP-SIDE) (R0259)
SPACER mm
TIGHTENING mm

SHOCK TOWER	UPPER SUS HOLDER SIDE SCREW	UPPER SUS HOLDER	FRONT
☐ STANDARD ☐ OPTION(WIDE)	☐ YES ☐ NO	☐ PLASTIC(1~2) ☐ ALUMINIUM	CAMBER deg.
UPPER PLATE OFFSET	TOE OUT deg.	MATERIAL ☐ NORMAL ☐ HARD	
☐ -1.5 ☐ 0 ☐ +1.5			
UPRIGHT ARM SPACER mm	SWING SHAFT ☐ 60mm ☐ 64mm ☐ 60mm ☐ 62mm (90°)	DOWN STOP mm	
CASTER ANGLE mm	UPRIGHT ARM POSITION ☐ CARBON ☐ ALUMINIUM	LOWER ARM PLATE ☐ STANDARD ☐ OPTION(WIDE)	
	☐ 1 ☐ 2 ☐ 3	MATERIAL ☐ NORMAL ☐ HARD	
	LOWER ARM HOLDER ☐ PLASTIC ☐ ALUMINIUM		
	☐ 1 ☐ 2		

SHOCK TOWER	BODY MOUNT POSITION	REAR
☐ STANDARD ☐ OPTION (REV)	☐ 1 ☐ 2 ☐ 3	CAMBER deg.
CENTERING POSITION mm	REAR HUB SPACER mm	
UPPER SUS POSITION ☐ WIDE ☐ NARROW	MATERIAL ☐ NORMAL ☐ HARD	
☐ 1 ☐ 2 ☐ 3		
LOWER ARM HOLDER ☐ STANDARD ☐ OPTION	SWING SHAFT ☐ 54mm ☐ 54mm(90°)	DOWN STOP mm
☐ 1 ☐ 2 ☐ 3	MATERIAL ☐ NORMAL ☐ HARD	
☐ 1 ☐ 2 ☐ 3	LOWER ARM PLATE ☐ IN SIDE ☐ MIDDLE ☐ OUT SIDE(STD)	
☐ SCREW	TOE IN deg.	

WEIGHT	CARBON STIFFENER	MAIN CHASSIS TYPE	CHASSIS
☐ MIDDLE ☐ RIGHT ☐ LEFT	☐ FRONT CARBON ☐ MIDDLE CARBON	☐ NORMAL (R0227) ☐ MULTIFLEX (R0227M)	UPPER PLATE TYPE & CUT
ADDITIONAL WEIGHT g	BATTERY PLATE TYPE & HOLD POSITION		
TOTAL CAR WEIGHT g			